


成品製造管制圖

DRAWING OF FINISHED PRODUCTS

禁止使用1級環境管理物質
 Non-use Warranty for Level 1
 Prohibited Substances in Product.

Pich 2.5mm
 間距 (.098")



產品編號 Part No: JP2540

品名 Product: 塑膠母座 - HOUSING

材質 Material: Housing: NYLON66 UL94V-0

配合端子 Suitable Terminal: J2540BS

配合塑膠 Suitable housing: JP24182

額定電壓/電流 Current Rating:

AC/DC250V 3A(22~28AWG#)

絕緣阻抗 INS. Resistance: 1000MΩ Min.

耐電壓 Withstand Voltage: 1000V AC/1minute.

適用溫度 Operation Temp: -25°C~+85°C

顏色 Colour: 本色 (Natural)

DIMENSION:(MM)

P:2.5 ± 0.1

W:5.1 ± 0.3

W1:8.0 ± 0.3

H:18.5 ± 0.3

PIN	A±0.3	B±0.2
2	5.8	2.5
3	8.3	5.0
4	10.8	7.5
5	13.3	10.0
6	15.8	12.5
7	18.3	15.0
8	20.8	17.5
9	23.3	20.0
10	25.8	22.5
11	28.3	25.0
12	30.8	27.5

* 本成品圖僅供參考,若需做為承認用請聯絡就近業務員確認

(The drawing is for reference only,

please contact the sales division nearby for final confirmation if it's for approval purpose.)

H/Q: Kaohsiung, Taiwan

總公司: 高雄, 台灣

TEL: 886-7-6223787

FAX: 886-7-6210385

E-mail: jmt6317@jmt.com.tw

Taipei Branch, Taiwan

台北營業所

TEL: 886-2-26940195-7

FAX: 886-2-26940738

E-mail: taipei.jmt@msa.hinet.net

Overseas, Taiwan

外銷業務部

TEL: 886-7-6223787

FAX: 886-7-6210385

E-mail: jmt6318@yahoo.com.tw