


成品製造管制圖
 DRAWING OF FINISHED PRODUCTS

禁止使用1級環境管理物質
 Non-use Warranty for Level 1
 Prohibited Substances in Product.

Pich 3.5mm
 間距 (.138")



產品編號 Part No: JM2350
 品名 Product: 塑膠公座-DIP CONNECTOR-DIP
 材質 Material: Housing: NYLON 94V-0
 Contact Pin: Brass, Tin plated.
 配合端子 Suitable Terminal: J2350PS
 配合塑膠 Suitable housing: JP2350
 額定電壓/電流 Current Rating:
 AC/DC600V 2A(24~28AWG#)
 絕緣阻抗 INS. Resistance: 1000MΩ Min.
 耐電壓 Withstand Voltage: 3800V AC/1minute.
 適用溫度 Operation Temp: -25°C~+85°C
 顏色 Colour: 本色 (Natural)

DIMENSION:(MM)

P: 3.5 ± 0.15
 T: □ 0.5 ± 0.05
 L: 7.7 ± 0.25
 L1: 6.5 ± 0.25
 L2: 1.0 ± 0.25
 W: 3.2 ± 0.2
 H: 10.6 ± 0.25
 H1: 3.4 ± 0.2
 H2: 1.5 ± 0.25

* 本成品圖僅供參考,若需做為承認用請聯絡就近業務員確認
 (The drawing is for reference only,
 please contact the sales division nearby for final confirmation if it's for approval purpose.)

H/Q: Kaohsiung, Taiwan
 總公司: 高雄, 台灣
 TEL: 886-7-6223787
 FAX: 886-7-6210385
 E-mail: jmt6317@jmt.com.tw

Taipei Branch, Taiwan
 台北營業所
 TEL: 886-2-26940195-7
 FAX: 886-2-26940738
 E-mail: taipei.jmt@msa.hinet.net

Overseas, Taiwan
 外銷業務部
 TEL: 886-7-6223787
 FAX: 886-7-6210385
 E-mail: jmt6318@yahoo.com.tw